

# Interchar<sup>®</sup> 1160

Thin film water-borne intumescent coating optimised  
for 60 minutes fire resistance

As part of the Interchar range for cellulosic fire protection, Interchar 1160 will maintain your architectural aesthetics for fire resistance up to 60 minutes on structural steelwork.

- Water-borne technology, approved to European fire test standards
- Zero VOC\* formulation reducing environmental impact
- Specifically suited for on-site applications due to minimised Health and Safety issues for other trades
- Compatible with a wide range of water-borne primers and a full topcoat colour range
- Fast drying characteristics for excellent productivity
- Single pack product for fast and easy single leg airless spray application
- **CE** Marked



# 60



# Interchar 1160

## fireproofing without compromising aesthetics

Interchar 1160 is a water-borne cellulosic fire protection which meets the need for a more sustainable approach to architectural fire protection for structural steel.

### Fire Protection with Aesthetic Appeal

- Competitive dry film thicknesses
- Applied as a thin layer, it does not compromise intricate designs and shapes allowing maximum architectural expression
- Fast drying formulation, quick return to service with majority of required thickness achievable in a single coat
- Compatible with a wide colour range of topcoats

### Sustainability and Health & Safety

- Water-borne, Zero VOC\* minimising environmental impact
- Low odour
- Halogen and borate free
- Compatible with a range of water-borne primers and full topcoat colour range in order to deliver a complete water-borne solution

\* According to EU Solvent Emission Directive (SED) 1999/13/EC

### Testing

EN 13381-8 Test Methods for determining the contribution to the fire resistance of structural members - Part 8: Applied reactive protection to steel members

ETAG 018 Part 2: Reactive Coatings for Fire Protection of Steel Elements

### Tested to the Highest Standards

Interchar is undergoing continual testing and approvals. Please contact International Paint for an up to date listing.



Deutsche Bank Place, Sydney Australia

### Typical Uses

Provides intumescent fire protection to structural steelwork while maintaining architectural aesthetics for commercial infrastructure assets including: -

- Airports
- Stadia and Leisure Facilities
- Office Buildings
- Retail Complexes

### One Supplier, One Solution

Project construction aspects and client aesthetic requirements may require the use of both a primer and coloured topcoats.

You can have confidence in International Paint because we test complete systems and can offer a single point supply and support.

This product has been developed in a controlled ISO 9001 Quality Approved laboratory environment. It has been tested in a UKAS approved laboratory and is manufactured to ISO 9002. International Paint makes no representation that the exhibited published test results, or any other tests, accurately represent results actually found in all field environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating(s).

[www.international-pc.com](http://www.international-pc.com)  
[protectivecoatings@akzonobel.com](mailto:protectivecoatings@akzonobel.com)

IP and International and all product names mentioned in this publication are trademarks of, or licensed to, AkzoNobel. © AKZONOBEL 2011.

International Protective Coatings has used its best endeavours to ensure that the information contained in this publication is correct at the time of printing. Please contact your local International Protective Coatings representative if you have any questions.

Unless otherwise agreed by us in writing, any contract to purchase products referred to in this brochure and any advice which we give in connection with the supply of products are subject to our standard conditions of sale.